



REDOIL

TECHNICAL DATA SHEET

MULTIAGRI UTTO 10W-30

Lubricant UTTO agricultural and earthmoving machinery



EELQMS

EUROPEAN ENGINE
LUBRICANTS SOCIETY
Data di prima emissione
19/11/2021
MANAGEMENT SYSTEM
Rev. N°4 del 01/07/2024

SPECIFICS

API GL-4 ALLISON C-4 Jhon Deere J20C, J20D Caterpillar TO-4
ZF TEML 03 E 03F 05F 06 E 06K 17E
CNH MAT 3525, 3526 ,3540 DEUTZ ALLIS FORD M2C 134D/M2C86/M2C134/M2C41B VOLVO
VCE VME WB 101 DENINSON HFO
Massey Ferguson : M1145 M1143 M1135 KUBOTA UDT FLUID VALTRA G2 G2-B10
VICKERS EATON I-280 DANFOS NEW HOLLAND 82948718 KOMATSU DRESSER B-06 0001-0002

TECHNICAL DESCRIPTION

Engineered formulation specifically designed for the lubrication of transmission units of modern tractors, agricultural and forestry machinery. This high-performance lubricant ensures the simultaneous lubrication of manual gears, hydrostatic systems, and oil-bath brakes. The technology used combines special base oils and advanced additives to guarantee maximum performance under heavy-duty and even the most extreme operating conditions.

The use of this product ensures the following benefits:

- Protection against molecular oxidation of the lubricant;
- Maximum thermal stability;
- Extended oil change intervals;
- Maximum detergency;
- Excellent dispersant, anti-corrosion, and anti-rust properties.



For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL

TECHNICAL DATA SHEET

MULTIAGRI UTTO 10W-30



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	Kg/dm ³	ASTMD7042	0,870
Viscosity 40°C	cSt	ASTMD445	79
Viscosity 100°C	cSt	ASTMD445	12
Viscosity Index	-	ASTMD2270	147
Flash Point	°C	ASTMD92	232
Freezing point	°C	ASTMD97	-30

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio
[Signature]